



超快恢复二极管

SF1002
SF1004
SF1006

ULTRAFAST
RECTIFIERS
10 AMPERES
200-400-600 VOLTS



TO-220AC

MAXIMUM RATINGS

Rating	Symbol	SF			Unit
		SF1002	SF1004	SF1006	
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_R	200	400	600	Volts
Average Rectified Forward Current Total Device, (Rated V_R), $T_C = 150^{\circ}C$	$I_F(AV)$	10			Amps
Peak Repetitive Forward Current (Rated V_R , Square Wave, 20 kHz), $T_C = 150^{\circ}C$	I_{FM}	20			Amps
Nonrepetitive Peak Surge Current (Surge applied at rated load conditions halfwave, single phase, 60 Hz)	I_{FSM}	130			Amps
Operating Junction Temperature and Storage Temperature	T_J, T_{stg}	-50 to +150			$^{\circ}C$

THERMAL CHARACTERISTICS

Maximum Thermal Resistance, Junction to Case	$R_{\theta JC}$	3.0	2.0	$^{\circ}C/W$
--	-----------------	-----	-----	---------------


ELECTRICAL CHARACTERISTICS

Maximum Instantaneous Forward Voltage (1) ($i_F = 10$ Amps, $T_C = 150^{\circ}C$) ($i_F = 10$ Amps, $T_C = 25^{\circ}C$)	V_F	0.895 0.975	1.00 1.30	1.20 1.50	Volts
Maximum Instantaneous Reverse Current (1) (Rated dc Voltage, $T_J = 150^{\circ}C$) (Rated dc Voltage, $T_J = 25^{\circ}C$)	i_R	250 5.0	500 10		μA
Maximum Reverse Recovery Time ($I_F = 1.0$ Amp, $di/dt = 50$ Amps/ μs) ($I_F = 0.5$ Amp, $i_R = 1.0$ Amp, $I_{REC} = 0.25$ Amp)	t_{rr}	35 25	60 50		ns

(1) Pulse Test: Pulse Width = 300 μs , Duty Cycle $\leq 2.0\%$.

Package Demensions

TO-220AC



Dimensions in Millimeters